

Data sheet

IM 053PN - PROFINET IO device (053-1PN01)

Technical data

Order no.	053-1PN01
Type	IM 053PN - PROFINET IO device
Module ID	-

General information

Note	-
Features	<p>Integrated 2-port switch Up to 64 peripheral modules Transfer rate 100Mbit/s full-duplex Supports MRP slave as MRP client, FMM (Free Module Mapping), Easy Maintenance Supports shared device with up to 3 connections Supports IRT (Isochronous Real Time communication) Supports multiple and single write (acyclic communication) Integrated Web server Integrated DC 24V power supply for power and electronic section supply of the periphery modules Status LEDs</p>

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	95 mA
Current consumption (rated value)	0.95 A
Inrush current	3.9 A
I^2t	0.14 A ² s
Max. current drain at backplane bus	3 A
Max. current drain load supply	10 A
Power loss	3 W

Status information, alarms, diagnostics

Status display	yes
Interrupts	yes, parameterizable
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Supply voltage display	green LED
Service Indicator	yellow LED
Group error display	red SF LED
Channel error display	none

Hardware configuration

Racks, max.	1
Modules per rack, max.	64
Number of digital modules, max.	64
Number of analog modules, max.	64

Communication

Fieldbus	PROFINET-IO
Type of interface	Ethernet 100 MBit

Connector	2 x RJ45
Topology	Line, Star
Electrically isolated	yes
Number of participants, max.	-
Node addresses	-
Transmission speed, min.	100 Mbit/s
Transmission speed, max.	100 Mbit/s
Address range inputs, max.	512 Byte
Address range outputs, max.	512 Byte
Number of TxPDOs, max.	-
Number of RxPDOs, max.	-
Supported profile	-
Supported transfer cycle	-
Cyclic data size per node	-
Max. Number of nodes	-
Supported communication method	-
Supported command "Cyclic"	-
Supported command "Event driven"	-
Supported command "Message"	-

Datasizes

Input bytes	-
Output bytes	-
Parameter bytes	-
Diagnostic bytes	-

Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	48.5 mm x 109 mm x 76.5 mm
Net weight	160 g
Weight including accessories	160 g
Gross weight	175 g

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes